

Enhance[™] Super Diesel Engine Oil

Description:

Enhance[™] Super Diesel Engine Oils are formulated with advanced additive technology recommended for use in current naturally aspirated and turbo-charged fourstroke diesel engines and four-stroke gasoline engines (Mixed Fleets) in which the SAE 15W-40 viscosity grade and API CK-4 service category are recommended. Enhance Super Diesel Engine Oil is also backwards compatible with diesel engines in which the API CJ-4, CI-4, CI-4 Plus and CH-4 service categories are recommended.

Enhance Super Diesel Engine Oil provides excellent performance in off-road service, including construction, forestry, mining, marine, and stationary power generation.

Applications:

Enhance[™] Super Diesel meets or exceeds the requirements of:

- API Service Categories: CK-4, CJ-4, CI-4 Plus, CI-4, CH-4
- ACEA: E9
- Caterpillar: ECF-3, ECF-2
- Cummins: CES 20086, 81
- Detroit Fluids Specification (DFS): 93K222, 93K218
- Volvo: VDS-4.5, VDS-4
- Mack: EOS-4.5, EO-O Premium Plus

| Enhance [™] Super Diesel Engine Oil | |
|---|--------|
| SAE Grade | 15W-40 |
| Kinematic Viscosity @ 40°C, mm ² /s | 115.6 |
| Kinematic Viscosity @ 100°C, mm ² /s | 15.3 |
| Dynamic Viscosity @ -20°C, mPa s | 6 200 |
| Viscosity Index | 138 |
| Flash Point (COC) °C | 237 |
| Pour Point °C | -36 |
| Density @ 15°C, kg/l | 0.875 |
| Total Base Number, mgKOH/g | 10 |

Typical Properties:

ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS